Appl. No. 10/736,501

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Cancelled)

2. (Currently Amended) ~~A method according to claim 1~~ A method of scheduling transmissions from a multi-beam transmitter to a plurality of receivers comprising:

determining an angle of departure for each of the plurality of receivers;

scheduling transmission to receivers based upon separation between angles of departure between scheduled receivers;

wherein a minimum angle of separation constraint is imposed that requires any two receivers which are scheduled during a given scheduling interval to have angles of departure separated by at least a first minimum angle of separation.

3. (Original) A method according to claim 2 wherein the receivers are scheduled by:

in sequence, selecting a receiver as a function of a performance metric, subject to said constraint.

4. (Original) A method according to claim 3 wherein the performance metric is cumulative throughput, and wherein in sequence, selecting a receiver as a function of the performance metric comprises:

a) determining a receiver with a lowest cumulative throughput and scheduling that receiver;

b) determining a receiver with a next lowest cumulative throughput and scheduling that receiver unless that receiver has an angle of separation with a previously scheduled receiver which does not satisfy the constraint;

c) repeating step b) for additional receivers.

2

Appl. No. 10/736,501

5. (Original)   A method according to claim 2 wherein the receivers are scheduled by, in sequence:

    a) scheduling a first receiver;

    b) determining a receiver of remaining receivers which has a largest angle of separation with previously scheduled receivers and scheduling that receiver subject to the constraint.

6. (Currently Amended)   A method according to claim 2 further comprising for each scheduling interval:

    logically dividing the receivers into low priority receivers and high priority receivers;

    scheduling the ~~low~~ high priority receivers before scheduling the ~~high~~ low priority receivers.

7. (Original)   A method according to claim 2 further comprising for each scheduling interval:

    logically dividing the receivers according to at least three groups each having a respective priority ranging from lowest to highest;

    scheduling the groups of receivers in decreasing order of priority.

8. (Original)   A method according to claim 6 wherein scheduling the high priority receivers comprises:

    a) determining a high priority receiver with a poorest performance metric and scheduling that receiver;

    b) determining a high priority receiver with a next poorest performance metric and scheduling that high priority receiver unless that high priority receiver has a minimum angle of separation with a previously scheduled receiver which does not satisfy the constraint; and

    wherein scheduling the low priority receivers comprises:

3

c) determining a low priority receiver which has a largest angle of separation with previously scheduled receivers and scheduling that user subject to the constraint.

9. (Original) A method according to claim 8 further comprising repeating step b) until there are no further high priority receivers that satisfy the constraints.

10. (Original) A method according to claim 9 further comprising repeating d) for further low priority receivers until no further low priority receiver satisfies the constraint or until there is no further capacity to schedule.

11. (Original) A method according to claim 2 applied to each of a plurality of sectors being serviced by a wireless network node.

12. (Original) A method according to claim 11 wherein the wireless network node is a network access point, and each receiver is a local access point.

13. (Original) A method according to claim 11 further comprising:

determining if there is any pair of receivers of different sectors which have angles of departure separated by less than a second minimum angle of separation;

for each such pair of receivers, eliminating one of the pair of receivers from consideration for scheduling.

14. (Original) A method according to claim 13 wherein the one of the pair of receivers eliminated from consideration is selected on the basis of cumulative throughput, with the receiver having higher cumulative throughput being eliminated.

15. (Original) A method according to claim 2 further comprising:

at a beginning of scheduling for each scheduling interval, eliminating at least one receiver from consideration for scheduling.

16. (Original) A method according to claim 8 applied to each of a plurality of sectors being serviced by a wireless network node, wherein the performance metric comprises cumulative

4

Appl. No. 10/736,501

throughput, the method further comprising:

determining if there is any pair of receivers of different sectors which have angles of departure separated by less than a second minimum angle of separation;

for each such pair of users, eliminating one of the pair of receivers from consideration for scheduling on the basis of cumulative throughput, with the higher cumulative throughput receiver of the pair being eliminated.

17. (Original) A method according to claim 2 wherein the multi-beam transmitter comprises an adaptive beamforming transmitter, the method further comprising performing adaptive beamforming for the scheduled receivers.

18. (Currently Amended)   A method according to claim 2 wherein the multi-beam transmitter generates a plurality of substantially fixed beams which are individually directable, the method further comprising directing each of the ~~statically-shaped~~ substantially fixed beams.

19. (Original) A method according to claim 2 wherein the multi-beam transmitter is a fixed multi-beam transmitter which generates an array of beams which are collectively steerable to a plurality of fixed rotational states, and individually activatable.

20. (Original) A transmitter adapted to implement a method according to claim ~~1~~ 2.

21. (Original) A transmitter according to claim 20 in the form of a network access point.

22. (Original) A system comprising:

a wireless network node adapted to implement a method according to claim ~~1~~ 2;

a plurality of receivers.

23. (Original) A system according to claim 22 wherein the wireless network node is a network access point, and each receiver is a local access point.

24. (Original) A computer readable medium having instructions stored thereon for implementing a method according to claim ~~1~~ 2.

5

Appl. No. 10/736,501

25. (Cancelled)

26. (Currently Amended)   ~~A transmitter according to claim 1~~ A transmitter comprising:

a multi-beam antenna;

a scheduler adapted to determine an angle of departure for each of a plurality of
receivers and to schedule transmission to each receiver on an appropriate beam of the multi-beam
antenna based upon separation between angles of departure between scheduled receivers;

wherein a minimum angle of separation constraint is imposed that requires any
two receivers which are scheduled during a given scheduling interval to have angles of departure
separated by at least a first minimum angle of separation.

27. (Original) A transmitter according to claim 26 wherein the scheduler is adapted to determine
an angle of departure for each receiver by receiving an angle of arrival information from each
receiver, and deriving the angle of departure from the angle of arrival information.

28. (Currently Amended)   A transmitter according to claim ~~25~~ 26 wherein the multi-beam
antenna is an adaptive beamforming antenna.

29. (Currently Amended)   A transmitter according to claim ~~25~~ 26 wherein the multi-beam
antenna is a fixed steering beam antenna.

30. (Currently Amended)   A transmitter according to claim ~~25~~ 26 wherein the multi-beam
antenna generates a plurality of beams having substantially fixed shapes which are individually
directable.

31. (Currently Amended)   A transmitter according to claim ~~25~~ 26 in the form of a network
access point.

6